

### **TECHNICAL SPECIFICATIONS 10 & 15 KVA SERVO STABILIZER**

<b>Capacity/Rating</b>	10 & 15 KVA
<b>General</b>	Single Phase Servo Voltage Stabilizer, suitable for indoor use, withstand ambient temp up to 55 degree C, oil cooled immersed in tank, control circuit for correction, suitable for balanced/ Unbalanced supply & load.
<b>Winding</b>	Copper Wound
<b>Input Voltage</b>	90-270V
<b>Input Frequency</b>	50Hz +/- 5%
<b>Output Voltage</b>	240V +/- 1%
<b>First Fill Oil</b>	Included
<b>Cooling</b>	ONAN
<b>Mounting</b>	Floor type
<b>Indication</b>	Mains ON indication on front panel.

#### **General Features**

- 1. Auto/ Manual Facility.**
- 2. Voltmeter/ Ampere meter on front panel.**
- 3. Solid State Control Circuit.**
- 4. High performance integrated circuit based, control system - No relays.**
- 5. Stepless Voltage correction at High speed without over shoot/hunting.**
- 6. High accuracy. No load to full load.**
- 7. Online serviceability with inter changeable plug-in Control Card.**
- 8. Burn proof/Brush less A.C. synchronous motor.**
- 9. Efficiency - better than 98.6%.**
- 10. Response time - less than 10 milli sec.**

**PRICE BID**

**Prices to be quoted inclusive of all taxes and duties and installation charges.**

<b>SL. NO</b>	<b>DESCRIPTION</b>	<b>Qty</b>	<b>Make of Offered</b>	<b>Rate (Rs.)</b>
1	Supply , Installation , testing & Commissioning of 10KVA & 15KVA servo Controlled Voltage Stabilizer, Single Phase Input & Single Phase output as technical specifications with <b>One year warranty:</b>			
	a) 10KVA	1 no.		
	b) 15KVA	1 no.		

Earnest Money Deposited CDR/FDR.....DATED.....

I/We have read all terms & conditions and filled bidder information page. All terms & conditions are acceptable to us.

Name of Proprietor/Partner.....

Name of Bidder.....

Address of Bidder.....

**Signature of Bidder**

**Seal of Bidder**